

- Rev B.1: 1. open U4 pin5 and add D15
- 2. update X2 part number
- 3. C30 and C31 changed to 3.3pF
- 4. change H1 and H4 size of footprint to C9D4.5
- 5. Update U10, U19 and U20 ESDALC6V1W5 with new footprint
- 6. add D11, D12, D13 for key and joystick button ESD protection

Title: MB1313


Project: STM32L4Rx-EV

Size: A3 Reference: MB1313 Rev:









Date: 10/1

Date: 10/10/20






Title: MCU		
Project: STM32L4Rx-EVAL		
Size: A3	Reference: MB1313	Revision: B.1
Date: 10/18/2017	Sheet: 2	of 16



Title: Power			
Project: STM32L4Rx-EVAL			
Size: A3	Reference: MB1313	Revision: B.1	Date: 7/12/2017
Sheet: 3 of 16			life.aumentec





Title: Memory & TFT LCD


Project: STM32L4Rx-EVAL

Size: A4 Reference: MB1313 Revision: B.1

Date: 3/31/2017



life.augmented




Operating range: 1.62<VDD<3.6V

Title: Audio		
Project: STM32L4Rx-EVAL		
Size: A4	Reference: MB1313	Revision: B.1
Date: 4/19/2017	Sheet: 5 of 16	



life. augmented

DSI LCD




Operating range:


1. GVO LCD IEG1120TB103GF-001 works at $1.65V < VDD < 3.3V$
2. MB1166 board works at $VDD = 3.3V$ only

Title: DSI LCD connector		
Project: STM32L4Rx-EVAL		
Size: A4	Reference: MB1313	Revision: B.1
Date: 7/12/2017	Sheet: 6	of 16


Buttons



LEDs




MICRO SD (TF) Card




MicroSD card

Operating Voltage: VDD no Lower than 2.7V



Joystick



Title: Peripherals


Project: STM32L4Rx-EVAL

Size: A4 | Reference: MB1313 | Revision: B.1


Date: 4/10/2017 | Sheet: 7 of 16




life.augmented



Potentiometer/LDR



ADC&DAC connector



Title: Analog and TS

Project: STM32L4Rx-EVAL


Size: A4

Reference: MB1313


Revision: B.1

Date: 6/5/2017


SWD



PWR




VUSB_ST_LINK









Power Switch to supply +5V from STLINK USB


LED_STLINK



COM









Title: JTAG & Trace		
Project: STM32L4Rx-EVAL		
Size: A4	Reference: MB1313	Revision: B.1
Date: 7/12/2017		Sheet: 11 of 16






life.augmented






Title: USB_OTG_FS		
Project: STM32L4Rx-EVAL		
Size: A4	Reference: MB1313	Revision: B.1
Date: 4/10/2017	Sheet: 13 of 16	







Title: Interface		
Project: STM32L4Rx-EVAL		
Size: A4	Reference: MB1313	Revision: B.1
Date: 7/12/2017		Sheet: 14 of 16



life.augmented





Title: Extension Connectors

Project: STM32L4Rx-EVAL

Size: A4 | Reference: MB1313 | Revision: B.1

Date: 3/31/2017



life.augmented